

Pleated Filter Cartridges – Flow-Max

Greater surface area for longer life and reduced filtration costs.

Standard 2-3/4" OD x 9-3/4" Length

MODEL NO.	MEDIA TYPE	MICRON RATING	NUMBER PER CASE
FM-1A-975	Synthetic	1 Absolute	24
FM-0.35-975	Synthetic	0.35	24
FM-1-975	Synthetic	1	24
FM-5-975	Synthetic	5	24
FM-20-975	Synthetic	20	24
FM-50-975	Synthetic	50	24
FM-100-975	Synthetic	100	24

Standard 2-3/4" OD x 19-1/2" Length

MODEL NO.	MEDIA TYPE	MICRON RATING	NUMBER PER CASE
FM-1-195	Synthetic	1	24
FM-5-195	Synthetic	5	24
FM-20-195	Synthetic	20	24

Standard 2-3/4" OD x 20" Length

MODEL NO.	MEDIA TYPE	MICRON RATING	NUMBER PER CASE
FM-1A-20	Synthetic	1 Absolute	24
FM-0.35-20	Synthetic	0.35	24
FM-1-20	Synthetic	1	24
FM-5-20	Synthetic	5	24
FM-20-20	Synthetic	20	24
FM-50-20	Synthetic	50	24

Standard 2-3/4" OD x 29-1/4" Length

MODEL NO.	MEDIA TYPE	MICRON RATING	NUMBER PER CASE
FM-1A-2925	Synthetic	1 Absolute	24
FM-0.35-2925	Synthetic	0.35	24
FM-1-2925	Synthetic	1	24
FM-5-2925	Synthetic	5	24
FM-20-2925	Synthetic	20	24
FM-50-2925	Synthetic	50	24

Standard 2-3/4" OD x 40" Length

MODEL NO.	MEDIA TYPE	MICRON RATING	NUMBER PER CASE
FM-1-40	Synthetic	1	24
FM-5-40	Synthetic	5	24
FM-20-40	Synthetic	20	24
FM-50-40	Synthetic	50	24

Specifications

Filter media	Synthetic (100% cellulose-free)
End caps	Plastisol (PVC)
Center tubes	Polypropylene
Temperature range	40°F - 140°F (4.4°C - 60°C)
Maximum Pressure	40 PSID
Recommended change out	20 - 30 PSID
Flow rate per 10" cartridge	3-10 GPM, depending on micron rating

