

Flow-Max Stainless Steel Filter Housings

Check Out These Many Features And Benefits:

- 100% stainless steel for durability.
- 304 and 316 stainless steel available.
- Convenient band clamp lid closure is standard for easy cartridge replacement.
- Pipe fittings are readily accessible for easy installation.
- Adjustable top plate accepts variable length cartridges for more options.
- Two drains provided for clean and dirty fluids.
- Legs and mounting tabs are available.
- Knife edge seals are provided at both ends of all DOE cartridges for superior performance.
- Rated for temperatures to 250° F. (No plastic holding rods.)
- Pressure rating to 150 psi.
- Housings for pressures to 300psi are available.
- Optional sanitary connections.
- Models to accept DOE, 222 and cartridges with 226 end caps.
- Protective poly-coat over stainless steel standard finish.
- Electro-polishing is available.
- Standard, Premium Series and Jumbo models are in stock for immediate shipment.



Specifications

Material	304 and 316 stainless steel are available.
Pressure rating	Housings are rated for pressures to 150 psi (10 bar).
Temperature	Filters are rated for temperatures to 250° F (121° C). Please consider cartridges to be used.
Gaskets & seals	Buna-N is standard. Viton, EDPM and Teflon are available.
Finish	Protective poly-coat over stainless is standard finish. Electro-polishing available.
Pressure drop	Initial pressure drop is <1 psi at designed flow rates for housings only.
Cartridge types	Housings are designed to accept DOE cartridges. Adapters for 222 & 226 cartridges available.

Models

