

Carbon Cartridges Selection Guide — cont.

Model No.	Brands	OD (IN)	Length (IN)	Flow Rate (GPM)	Micron Rating (Nominal)	Reduction of			
						Chlorine Reduction Gallon Rating *	Cyst	VOC	Lead
4-1/2 IN OD Cartridges									
S7812	Pentair	4 1/2	9 3/4	2	20	12,500			
S7816	Pentair	4 1/2	9 3/4	2	25	35,000			
GAC-BB10	Watts	4 1/2	9 3/4	3	-	7,500			
WCBCFF975	Watts	4 1/2	9 3/4	4	5	10,000			
S7814	Pentair	4 1/2	20	4	20	25,000			
S7815	Pentair	4 1/2	20	4	25	70,000			
GAC-BB20	Watts	4 1/2	20	5	-	15,000			
WCBCFF20	Watts	4 1/2	20	8	5	20,000			
4-5/8 IN OD Cartridges									
S7817X	Pentair	4 5/8	9 3/4	2	5	22,000			
S7845	Pentair	4 5/8	9 3/4	2	10	15,000			
MAXCL-FF975	C-MAX	4 5/8	9 3/4	4	0.5	70,000			
MAXETW-FF975	C-MAX	4 5/8	9 3/4	4	5	11,000			
MAXPB-FF20	C-MAX	4 5/8	20	2	0.5	150,000	✓		✓
S7811XA	Pentair	4 5/8	20	4	5	40,000			
MAXCL-FF20	C-MAX	4 5/8	20	8	0.5	150,000			
MAXETW-FF20	C-MAX	4 5/8	20	8	5	20,000			
Inline Encapsulated Cartridges									
CL6ROT33	Watts	2	6	0.5		✓			
K2333JJ	Watts	2	6	0.75		✓			
CL10ROT33	Watts	2	10	0.5	5	✓			
K2533SS	Watts	2	10	0.5		✓			
AICRO	Watts	2	10	0.75		✓			
AICRO-JGK	Watts	2	10	0.75		✓			
GS10ROB	Watts	2	10	0.75		✓			
SCL10	Watts	2	10	0.75		✓			
GS10CAL/ROB	Watts	2	10	0.75		✓			
K2533JJ	Watts	2	10	0.75		✓			
Quick-Change Encapsulated Proprietary Cartridges									
WQCABC10	Watts	2 1/2	10		5	✓			
WQCCC10	Watts	2 1/2	10		5	1,500			
WQCGAC10	Watts	2 1/2	10			✓		✓	
WQCABC11	Watts	2 1/2	11		5	✓			
WQCCC11	Watts	2 1/2	11		5	2,000			
WQCGAC11	Watts	2 1/2	11			✓		✓	
WQCABC13	Watts	2 1/2	13		5	✓			
WQCCC13	Watts	2 1/2	13		5	2,500			
WQCGAC13	Watts	2 1/2	13			✓		✓	
Quick-Change Hollow Fiber Membrane Cartridges									
WQCHFC10	Watts	2 1/2	10	0.1					
WQCHFC11	Watts	2 1/2	11	0.1					
WQCHFC13	Watts	2 1/2	13	0.1					

* For individual chlorine claims see individual product page