

## Carbon Block Filters - C-Max

Full line of solid block activated carbon cartridges for water treatment.



Standard cartridges



Full-Flow(B-B)

Full Product Line With Color Coded End Caps To Indicate Cartridge Type



MAX-ETW



MAX-CYST



MAX-VOC



MAX-T



MAX-PB



MAX-CL

### Cartridge Selection Guide

CARTRIDGE TYPE	WALL	CARBON TYPE	MICRON	PARTICLE SIZE	VERY HIGH SEDIMENT REMOVAL	VERY HIGH CHLORINE REDUCTION	CYSTS	VOCS	LEAD
MAXETW	Thick	Coconut shell	5	Medium					
MAXCYST	Thick	Coconut shell	0.5	Fine			•		
MAXVOC	Thick	Coconut shell	0.5	Fine			•	•	
MAXT	Thick	Coconut shell	5	Medium					
MAXPB	Thick	Coconut shell	0.5	Fine			•		•
MAXCL	Thick	Coconut shell	0.5	Fine		•			



C-MAX® carbon block cartridges are tested and certified by NSF International under NSF / ANSI Standard 42 for materials only. Performance claims are supported by company test results.

**NOTICE**

C-MAX cartridges are rated for temperatures to 165°F (74°C).