

**NEW!**

# ULTRAPEN™ PT5

**Dissolved Oxygen (DO)  
and Temperature Pen**

*Professional Water Analysis*

## HIGH PERFORMANCE FEATURES

- Industry Leading Accuracy
- Adjustable for Altitude and Salinity
- 3 Calibration Methods: Air, Water and 0 ppm DO
- Dynamic Membrane Temperature Correction
- Easy to Use - One Button Control
- Waterproof
- Rugged Design with Aircraft Aluminum Body
- Proprietary Sensor Design

## PT5 COMES WITH:

- PT5 Pocket Tester Pen - Battery Installed
- Protective Cap
- Pocket Clip
- Holster
- Lanyard
- Operating Instructions



instrument shown larger than actual size

### ALSO AVAILABLE!

**ULTRAPEN™ PT1**  
Conductivity, TDS, Salinity  
& Temperature



**ULTRAPEN™ PT2**  
pH & Temperature



**ULTRAPEN™ PT3**  
ORP & Temperature



**ULTRAPEN™ PT4**  
Free Chlorine Equivalent (FC)  
& Temperature



**MYRON L METERS.com**  
The Water Quality Experts


## PT5 MEASUREMENT MODES

Mode	PARAMETER MEASURED
Hold	Displays real-time readings until stable or 3 minutes, whichever ever comes first, then displays final readings.
LIVE	Displays real-time readings continuously for up to 5 minutes.

## PT5 PARAMETER MODES

Mode	PARAMETER MEASURED
DO Default	Display alternates between DO Concentration in ppm, DO Saturation in % and Temperature.
DO Concentration	Display alternates between DO Concentration in ppm and Temperature.
DO Saturation	Display alternates between DO Saturation in % and Temperature.

## SPECIFICATIONS

Measurement Range:	DO Concentration: 0 - 20 ppm, DO Saturation 0 - 200% Temperature: 0 - 71° C / 32 - 160° F
Accuracy:	DO: ± 2% of Reading, Temperature: ± 0.1°C / ± 0.1°F
Repeatability:	DO: ± 1% of Reading, Temperature: ± 0.1°C / ± 0.1°F
Resolution:	DO Concentration: 0.01 ppm, DO Saturation 0.1% Temperature ± 0.1°C / ± 0.1°F
Altitude Adjustment:	-2,000 ft to 15,000 ft: increments of 100 ft
Salinity Adjustment:	0 - 50 ppt increments of 1 ppt
Time to Reading Stabilization:	10 - 180 seconds
Active Mode Power Consumption:	Active Mode: 33 - 140 mA, Sleep Mode: 2 µA
Temperature Adjustment for Membrane permeability:	Automatic
Physical Dimensions:	17.15 cm L x 1.59 cm D or 6.75 in. L x .625 in. D
Weight:	57.4 g or 2 oz
Case Material:	Anodized Aluminum with Protective Coating
Battery Type:	N type, Alkaline 1.5 V
Calibration Methods:	1 or 2 Point; 0 ppm DO Calibration Solution and/or air or water
Operating Temperature:	DO Saturation: 0 - 60°C / 32 - 140°F; DO Concentration: 0 - 40°C / 32 - 104°F
Storage Temperature:	0 - 55°C / 32 - 131°F
Water Resistance:	IP67 and NEMA 6
EN61236-1: 2006 - Annex A: 2008; 1999/5/EC Annex III	 Electrostatic discharge to case of instrument may cause PT5 to spontaneously power on. In this case, the PT5 will power off after several seconds

## ACCESSORIES

### STANDARD SOLUTIONS:

Order Model:

DOSOL 0 ppm Dissolved Oxygen Calibration Solution

### REPLACEMENT ITEMS AND CONSUMABLE ITEMS:

Order Models:

DOM5 DO Membrane 5pk.

DOSRE DO Sensor Replenishment Electrolyte 2 oz.

DORS DO Replenishment Syringe w/Tip

DOM5K DO Membrane 5pk, Replenishment Electrolyte 2 oz, Syringe w/Tip Kit.

## MYRON L® WARRANTY

The PT5, excluding the Sensor and Battery, has a one (1) year limited warranty.

3460 Marron Road, Suite 103-341

Oceanside, CA 92056 USA

Tel: +1-866-907-5459

Fax: +1-888-256-8238

www.myronl.com

Printed in U.S.A.

**Built On Trust.** Founded in 1957, the Myron L® Company is one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

